



ITEM	SELECTABLE CONTENTS
DISPLAY MODE	STN YELLOW MODE STN GRAY MODE STN BLUE MODE FSTN
POLARIZER TYPE	REFLECTIVE TRANSPARENT TRANSMISSIVE POSITIVE TRANSMISSIVE NEGATIVE
VIEWING DIRECTION	6 O'CLOCK 12 O'CLOCK
LED BACKLIGHT	WHITE Y-G RED GREEN AMBER
TEMPERATURE RANGE	STANDARD TEMPERATURE WIDE TEMPERATURE
OPERATING VOLTAGE	5.0V
LED DRIVING VOLTAGE	6.5V
LED DRIVE METHOD	1/32 DUTY, 1/5 BIAS
LCD DRIVE IC	PT6520 OR EQUIV

NOTE:
1. The power supply for backlight is depended on the backlight color and the value of current-limiting resistance.

THE PART NUMBER IN MASS PRODUCTION	
1.STN(GRAY)/POSITIVE/TRANSPARENT;BL:Y-G LED BACKLIGHT;6 O'CLOCK;	
2.FSTN/POSITIVE/TRANSPARENT;BL:WHITE LED BACKLIGHT;12 O'CLOCK;	
UNIT	TOLERANCE
MM	X.X = ±0.2
3RD ANGLE	X.XX = ±0.10
ANG =	-
SCALE:	1:1
DRAWN:	TITLE:
CHECKED:	MODEL NO: AGM1232G SERIES
APPROVED:	PART NO:
DISPLAYTRONIC	
XIAMEN ZETTLER ELECTRONICS CO., LTD.	
LCM	
REV	A
SH NO	1/1