

<p>1</p> <p>2</p> <p>3</p> <p>4</p> <p>5</p> <p>6</p> <p>7</p> <p>8</p>			<p>Display Pattern</p>	<table border="1"> <thead> <tr> <th>ITEM</th> <th>T1</th> <th>T2</th> </tr> </thead> <tbody> <tr> <td>BACKLIGHT</td> <td>10.5</td> <td>13.5</td> </tr> <tr> <td>WITHOUT BL</td> <td>6.2</td> <td>9.0</td> </tr> </tbody> </table>	ITEM	T1	T2	BACKLIGHT	10.5	13.5	WITHOUT BL	6.2	9.0	<table border="1"> <thead> <tr> <th>ITEM</th> <th>SELECTABLE CONTENTS</th> </tr> </thead> <tbody> <tr> <td>DISPLAY MODE</td> <td>STN YELLOW MODE STN GRAY MODE STN BLUE MODE FSTN</td> </tr> <tr> <td>POLARIZER TYPE</td> <td>REFLECTIVE TRANSMISSIVE TRANSMISSIVE, POSITIVE TRANSMISSIVE, NEGATIVE</td> </tr> <tr> <td>VIEWING DIRECTION</td> <td>6 O'CLOCK 12 O'CLOCK WHITE Y-G RED GREEN BLUE AMBER TRI-COLOR</td> </tr> <tr> <td>TEMPERATURE RANGE</td> <td>STANDARD TEMPERATURE WIDE TEMPERATURE ENGLISH-JAPANESE FONTS ENGLISH-EUROPEAN FONTS ENGLISH-RUSSIAN FONTS CYRILLIC FONTS HEBREW FONTS</td> </tr> <tr> <td>CHARACTER PATTERNS</td> <td>ENGLISH-JAPANESE FONTS ENGLISH-EUROPEAN FONTS ENGLISH-RUSSIAN FONTS CYRILLIC FONTS HEBREW FONTS</td> </tr> <tr> <td>OPERATING VOLTAGE</td> <td>5V</td> </tr> <tr> <td>LCD DRIVING VOLTAGE</td> <td>4.5V</td> </tr> <tr> <td>LCD DRIVE METHOD</td> <td>1/16 DUTY 1/5 BIAS</td> </tr> <tr> <td>LCD DRIVE IC</td> <td>SPLC780D-001 OR EQUIV</td> </tr> </tbody> </table> <p>NOTE:</p> <ol style="list-style-type: none"> The backlight can be driven by pin A, pin K or pin 1, pin 2 which is selectable. The voltage of backlight is depended on the backlight color and the value of current-limiting resistance. The operating voltage can be driven by 3.3v which is selectable. 	ITEM	SELECTABLE CONTENTS	DISPLAY MODE	STN YELLOW MODE STN GRAY MODE STN BLUE MODE FSTN	POLARIZER TYPE	REFLECTIVE TRANSMISSIVE TRANSMISSIVE, POSITIVE TRANSMISSIVE, NEGATIVE	VIEWING DIRECTION	6 O'CLOCK 12 O'CLOCK WHITE Y-G RED GREEN BLUE AMBER TRI-COLOR	TEMPERATURE RANGE	STANDARD TEMPERATURE WIDE TEMPERATURE ENGLISH-JAPANESE FONTS ENGLISH-EUROPEAN FONTS ENGLISH-RUSSIAN FONTS CYRILLIC FONTS HEBREW FONTS	CHARACTER PATTERNS	ENGLISH-JAPANESE FONTS ENGLISH-EUROPEAN FONTS ENGLISH-RUSSIAN FONTS CYRILLIC FONTS HEBREW FONTS	OPERATING VOLTAGE	5V	LCD DRIVING VOLTAGE	4.5V	LCD DRIVE METHOD	1/16 DUTY 1/5 BIAS	LCD DRIVE IC	SPLC780D-001 OR EQUIV
ITEM	T1	T2																																
BACKLIGHT	10.5	13.5																																
WITHOUT BL	6.2	9.0																																
ITEM	SELECTABLE CONTENTS																																	
DISPLAY MODE	STN YELLOW MODE STN GRAY MODE STN BLUE MODE FSTN																																	
POLARIZER TYPE	REFLECTIVE TRANSMISSIVE TRANSMISSIVE, POSITIVE TRANSMISSIVE, NEGATIVE																																	
VIEWING DIRECTION	6 O'CLOCK 12 O'CLOCK WHITE Y-G RED GREEN BLUE AMBER TRI-COLOR																																	
TEMPERATURE RANGE	STANDARD TEMPERATURE WIDE TEMPERATURE ENGLISH-JAPANESE FONTS ENGLISH-EUROPEAN FONTS ENGLISH-RUSSIAN FONTS CYRILLIC FONTS HEBREW FONTS																																	
CHARACTER PATTERNS	ENGLISH-JAPANESE FONTS ENGLISH-EUROPEAN FONTS ENGLISH-RUSSIAN FONTS CYRILLIC FONTS HEBREW FONTS																																	
OPERATING VOLTAGE	5V																																	
LCD DRIVING VOLTAGE	4.5V																																	
LCD DRIVE METHOD	1/16 DUTY 1/5 BIAS																																	
LCD DRIVE IC	SPLC780D-001 OR EQUIV																																	
<p>1</p> <p>2</p> <p>3</p> <p>4</p> <p>5</p> <p>6</p> <p>7</p> <p>8</p>	<p>THE PART NUMBER IN MASS PRODUCTION</p> <p>1.Y-G OR GRAY STN, TRANSMISSIVE LCD; WHITE BACKLIGHT; 6 O'CLOCK OR 12 O'CLOCK;</p> <p>2.FSTN, TRANSMISSIVE LCD; WHITE BACKLIGHT; 6 O'CLOCK;</p> <p>3.GRAY STN, TRANSMISSIVE LCD; WHITE BACKLIGHT; 12 O'CLOCK;</p> <p>4.BLUE STN, TRANSMISSIVE NEGATIVE LCD; WHITE BACKLIGHT; 6 O'CLOCK;</p> <p>5.Y-G OR GRAY STN, REFLECTIVE LCD; WITHOUT BACKLIGHT; 6 O'CLOCK OR 12 O'CLOCK;</p> <p>6.FSTN, TRANSMISSIVE LCD; TRI-COLOR BACKLIGHT; 6 O'CLOCK;</p>	<p>UNIT: MM</p> <p>3RD ANGLE</p> <p>SCALE: 1:1</p> <p>DRAWN: _____</p> <p>CHECKED: _____</p> <p>APPROVED: _____</p>	<p>TOLERANCE</p> <p>X.X = ±0.2</p> <p>X.XX = ±0.10</p> <p>ANG = -</p>	<p>DISPLAYTRONIC</p> <p>XIAMEN ZETTLER ELECTRONICS CO., LTD.</p> <p>TITLE: LCM</p> <p>MODEL NO: ACM0802C SERIES</p> <p>PART NO: _____</p>																														