



16	LED-
15	LED+
14	DB7
13	DB6
12	DB5
11	DB4
10	DB3
9	DB2
8	DB1
7	DB0
6	E
5	R/W
4	RS
3	V0
2	VDD
1	VSS

THE PART NUMBER IN MASS PRODUCTION

1.Y-G STN, TRANSFLECTIVE LCD;Y-G BACKLIGHT;6 O'CLOCK;

UNIT	TOLERANCE
MM	X.X = ±0.2
3RD ANGLE	X.XX = ±0.10
ANG	ANG = -

SCALE: 1:1

TITLE: LCM

MODEL NO: ACM1202K SERIES

PART NO: SH NO 1/1

DISPLAYTRONIC

XIAMEN ZETTLER ELECTRONICS CO., LTD.

DRAWN: A

CHECKED: A

APPROVED: A

1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---

ITEM	SELECTABLE CONTENTS
DISPLAY MODE	STN YELLOW MODE STN GRAY MODE STN BLUE MODE FSTN
POLARIZER TYPE	REFLECTIVE TRANSFLECTIVE TRANSMISSIVE, POSITIVE TRANSMISSIVE, NEGATIVE
VIEWING DIRECTION	6 O'CLOCK 12 O'CLOCK WHITE Y-G RED GREEN AMBER TRI-COLOR
LED BACKLIGHT	STANDARD TEMPERATURE WIDE TEMPERATURE ENGLISH-JAPANESE FONTS ENGLISH-EUROPEAN FONTS ENGLISH-RUSSIAN FONTS CYRILLIC FONTS HEBREW FONTS
TEMPERATURE RANGE	3.3V 4.5V
CHARACTER PATTERNS	1/16 DUTY 1/5 BIAS SPLC783A-001A OR EQUIV
OPERATING VOLTAGE	NOTE: 1. The voltage of backlight is depended on the backlight color and the value of current-limiting resistance.
LED DRIVING VOLTAGE	
LCD DRIVE METHOD	
LCD DRIVE IC	