



1	2	3	4	5	6	7	8																				
THE PART NUMBER IN MASS PRODUCTION																											
1.STN(Y-G)/POSITIVE/TRANSFLECTIVE ;BL:Y-G LED BACKLIGHT;6 O'CLOCK;																											
UNIT				TOLERANCE																							
MM				X.X = ±0.2																							
3RD ANGLE				X.XX = ±0.10																							
SCALE: 1:1				ANG = -																							
DRAWN:				TITLE: LCM																							
CHECKED:				MODEL NO: AGM1232T SERIES																							
APPROVED:				PART NO:																							
				SH NO 1/1																							
<table border="1"> <tr> <td>ITEM</td> <td>SELECTABLE CONTENTS</td> </tr> <tr> <td>DISPLAY MODE</td> <td>STN YELLOW MODE STN GRAY MODE STN BLUE MODE FSTN</td> </tr> <tr> <td>POLARIZER TYPE</td> <td>REFLECTIVE TRANSPARENT TRANSMISSIVE, POSITIVE TRANSMISSIVE, NEGATIVE</td> </tr> <tr> <td>VIEWING DIRECTION</td> <td>6 O'CLOCK 12 O'CLOCK WHITE Y-G RED GREEN BLUE AMBER</td> </tr> <tr> <td>LED BACKLIGHT</td> <td>TRICOLOR</td> </tr> <tr> <td>TEMPERATURE RANGE</td> <td>STANDARD TEMPERATURE WIDE TEMPERATURE</td> </tr> <tr> <td>OPERATING VOLTAGE</td> <td>5.0V</td> </tr> <tr> <td>LED DRIVING VOLTAGE</td> <td>6.5V</td> </tr> <tr> <td>LED DRIVE METHOD</td> <td>1/32 DUTY, 1/5 BIAS</td> </tr> <tr> <td>LED DRIVE IC</td> <td>PT6520 OR EQUIV</td> </tr> </table>								ITEM	SELECTABLE CONTENTS	DISPLAY MODE	STN YELLOW MODE STN GRAY MODE STN BLUE MODE FSTN	POLARIZER TYPE	REFLECTIVE TRANSPARENT TRANSMISSIVE, POSITIVE TRANSMISSIVE, NEGATIVE	VIEWING DIRECTION	6 O'CLOCK 12 O'CLOCK WHITE Y-G RED GREEN BLUE AMBER	LED BACKLIGHT	TRICOLOR	TEMPERATURE RANGE	STANDARD TEMPERATURE WIDE TEMPERATURE	OPERATING VOLTAGE	5.0V	LED DRIVING VOLTAGE	6.5V	LED DRIVE METHOD	1/32 DUTY, 1/5 BIAS	LED DRIVE IC	PT6520 OR EQUIV
ITEM	SELECTABLE CONTENTS																										
DISPLAY MODE	STN YELLOW MODE STN GRAY MODE STN BLUE MODE FSTN																										
POLARIZER TYPE	REFLECTIVE TRANSPARENT TRANSMISSIVE, POSITIVE TRANSMISSIVE, NEGATIVE																										
VIEWING DIRECTION	6 O'CLOCK 12 O'CLOCK WHITE Y-G RED GREEN BLUE AMBER																										
LED BACKLIGHT	TRICOLOR																										
TEMPERATURE RANGE	STANDARD TEMPERATURE WIDE TEMPERATURE																										
OPERATING VOLTAGE	5.0V																										
LED DRIVING VOLTAGE	6.5V																										
LED DRIVE METHOD	1/32 DUTY, 1/5 BIAS																										
LED DRIVE IC	PT6520 OR EQUIV																										
NOTE:																											
1. The power supply for backlight is depended on the backlight color and the value of current-limiting resistance.																											

DISPLAYTRONIC

XIAMEN ZETTLER ELECTRONICS CO., LTD.

LCM

TITLE: LCM
MODEL NO: AGM1232T SERIES
PART NO:

18	LED+(GV)
17	LED-
16	DB7
15	DB6
14	DB5
13	DB4
12	DB3
11	DB2
10	DB1
9	DB0
8	A0
7	R/W
6	E2
5	E1
4	RST
3	V0
2	VSS
1	VDD
	PIN SYMBOL

UNIT		TOLERANCE	
MM		X.X = ±0.2	
3RD ANGLE		X.XX = ±0.10	
SCALE: 1:1		ANG = -	
DRAWN:		TITLE: LCM	
CHECKED:		MODEL NO: AGM1232T SERIES	
APPROVED:		PART NO:	
		SH NO 1/1	

1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---