



ITEM	SELECTABLE CONTENTS
DISPLAY MODE	STN YELLOW MODE STN GRAY MODE STN BLUE MODE FSTN
POLARIZER TYPE	REFLECTIVE TRANSPARENT TRANSMISSIVE POSITIVE TRANSMISSIVE NEGATIVE
VIEWING DIRECTION	6 O'CLOCK 12 O'CLOCK
LED BACKLIGHT	WHITE Y-G RED GREEN BLUE AMBER
TEMPERATURE RANGE	STANDARD TEMPERATURE WIDE TEMPERATURE
OPERATING VOLTAGE	5.0V
LED DRIVING VOLTAGE	5.0V
LED DRIVE METHOD	1/17DUTY-1/5BIAS
LED DRIVE IC	ST7522 OR EQU

NOTE:
1. The power supply for backlight is depended on the backlight color and the value of current-limiting resistance.

THE PART NUMBER IN MASS PRODUCTION
1.FSTN/POSITIVE/TRANSPARENT;2.BL;RED LED BACKLIGHT;6 O'CLOCK;

UNIT	TOLERANCE
MM	X.X = ±0.2
3RD ANGLE	X.XX = ±0.10
ANG	= -

DISPLAYTRONIC
XIAMEN ZETTLER ELECTRONICS CO., LTD.

SCALE:	1:1
DRAWN:	
CHECKED:	
APPROVED:	
TITLE:	LCM
MODEL NO:	AGM9508A SERIES
PART NO:	

PIN	SYMBOL
1	VSS
2	VDD
3	NC
4	AO
5	E
6	NC
7	Heater(+)
8	Heater(+)
9	R/W
10	DB0
11	DB1
12	DB2
13	DB3
14	DB4
15	DB5
16	DB6
17	DB7
18	RES
19	AGSV)
20	K

REV	A
SH NO	1/1