



1	2	3	4	5	6	7	8
<p>THE PART NUMBER IN MASS PRODUCTION</p> <p>1.FSTN/POSITIVE/TRANSMISSIVE ;BL:TRI-COLOR LED BACKLIGHT;12 O'CLOCK;</p>							
UNIT		TOLERANCE					
MM		X.X = ±0.2					
3RD ANGLE		X.XX = ±0.10					
SCALE: 1:1		ANG = -					
DRAWN:		TITLE: LCM		XIAMEN ZETTLER ELECTRONICS CO., LTD.			
CHECKED:		MODEL NO: AGM9648A SERIES		REV A			
APPROVED:		PART NO:		SH NO 1/1			
<p>ITEM SELECTABLE CONTENTS</p> <p>DISPLAY MODE STN YELLOW MODE</p> <p>STN GRAY MODE</p> <p>STN BLUE MODE</p> <p>FSTN</p> <p>POLARIZER TYPE REFLECTIVE</p> <p>TRANSELECTIVE</p> <p>TRANSMISSIVE, POSITIVE</p> <p>TRANSMISSIVE, NEGATIVE</p> <p>VIEWING DIRECTION 6 O'CLOCK</p> <p>12 O'CLOCK</p> <p>WHITE</p> <p>Y-G</p> <p>RED</p> <p>GREEN</p> <p>BLUE</p> <p>AMBER</p> <p>TRICOLOR</p> <p>TEMPERATURE RANGE STANDARD TEMPERATURE</p> <p>WIDE TEMPERATURE</p> <p>OPERATING VOLTAGE 5.0V</p> <p>LED DRIVING VOLTAGE 9.0V</p> <p>LED DRIVE METHOD 1/6SDUTY 1/9BIAS</p> <p>LED DRIVE I.C EPL65132 OR EQU</p>							
<p>NOTE:</p>							

1	2	3	4	5	6	7	8
<p>RGB BACKLIGHT</p> <p>LCD DISPLAY</p> <p>96X48 DOTS</p> <p>COM33~COM65</p> <p>EPL65132</p> <p>COM1~COM32</p> <p>VDD</p> <p>VSS</p> <p>P/S</p> <p>C86</p> <p>RST</p> <p>D7</p> <p>D6</p> <p>D5</p> <p>D4</p> <p>D3</p> <p>D2</p> <p>D1</p> <p>D0</p> <p>CS</p> <p>A0</p> <p>WR</p> <p>RD</p> <p>KB</p> <p>KG</p> <p>KR</p>							